



The ANC-606V / ANC-606G is a 3GPP/ISMA-compatible network camera, offering superior image quality and efficient bandwidth by MPEG4 implementation. Users can easily access it and receive synchronized video and audio by computers, cell phones, or media adapters with TV, anytime, anywhere for indoor surveillance and remote monitoring.

Network Camera



3GPP/ISMA

ANC-606V/ANC-606G

Features

- Live Video and Audio Monitoring via 2.5G/3G Mobile Phone or Media Adapter
- MPEG-4 Video Compression (Simple Profile)
- Compact Size with Stylish Design
- Easy to Install and Configure
- Optimized Synchronization of Audio and Video
- 802.11g Wireless Connection (ANC-606G)
- Supports 3GPP/ISMA RTSP (3rd Generation Partnership Project) (Internet Streaming Media Alliance) (Real Time Streaming Protocol)
- Intelligent Motion Detection
- Superior Low Light Performance
- Excellent Image Quality with Up to 30 Frames Per Second in VGA Resolution



3GPP/ISMA Network Camera

ANC-606V/ANC-606G



- Cellphone with 3GPP player
- ISMA compliant devices
- Real Player 10.5
- Quick Time 6.5
- Packet Video Player 3.3
- ★ 3GPP / ISMA Function Ready
- ★ Applications depend on local ISP provider service.



Technical Specifications

Models

- ANC-606V (Wired)
- ANC-606G (Wireless)

System

- CPU: VVTK-1000 SoC
- RAM: 32MB SDRAM
- ROM: 4MB FLASHROM

Networking

- Protocols
UPnP, TCP/IP, RTSP/RTP/RTCP, HTTP, SMTP, FTP
Telnet, NTP, DNS, DDNS, DHCP and PPPoE
- Ethernet
10 baseT or 100 baseT Fast Ethernet auto negotiation
- Wireless (ANC-606G)
802.11g wireless LAN

Video

- Algorithm
MPEG4 simple profile for streaming video
JPGE for still image
- Features
Adjustable image size, quality and bit-rate
Time stamp and text caption
Three configurable motion detection windows
Flip & mirror
- Resolution
Up to 30/25 frames at 160x120
Up to 30/25 frames at 176x144
Up to 30/25 frames at 320x240
Up to 30/25 frames at 640x480

Camera Specifications

- 1/4" color CMOS sensor
- Resolution: 640(H)x480(V)
- 5Lux/F2.0
- AGC/AWB/AES
- Electronic Shutter: 1/60 to 1/15,000 secretary.

Lens

- 4.0mm, F2.0

Audio

- Algorithm
GSM-AMR/MPEG4 AAC
- Supports audio mute

Microphone

- Omni-directional
- Frequency
50~16000Hz
- S/N ratio
More than 60dB

Security

- ID/Password authentication

LED Indicator

- Two color system status indicators

Dimensions

- Depth: 34.8mm
- Width: 109.5mm
- Height: 77.2mm

Weight

- Net: 150g (ANC-606V)
- Net: 165g (ANC-606G)

Power

- 5VDC

Operating Environments

- Temperature: 0o~ 50oC (32o~ 122oF)
- Humidity: 85% RH

EMI & Safety

- CE, FCC

Viewing System Requirements

- Operating system: Microsoft Windows 98 SE, ME, 2000, XP
- Browser: Internet Explorer 5.0 or above
- Cellphone: 3GPP player
- Real Player 10.5
- Quick Time 6.5
- Packet Video Player 3.0



ANC-606V



ANC-606G

Made In Taiwan



AFREY
聯研國際科技股份有限公司

6F, No.249, Chien I Road., Chung Ho City, Taipei,
Taiwan, R.O.C.
TEL: 886-2-3234-2966
FAX: 886-2-8227-7858/ 8227-7859
E-mail: sales@afrey.com.tw

All specifications are subject to change without notice.
All other trademarks are owned by their respective companies.